



The Clear Choice Is Crystal


 National Fenestration Rating Council® CERTIFIED	Crystal Pacific Window & Door System, Inc. Vista / Vista PLUS Sliding Door Vinyl Frame Double Glazing (DS-DS)-Argon-LoE ³ -366™ CPW-M-2-00017-00001	
	ENERGY PERFORMANCE RATINGS	
U-Factor (U.S./I-P) 0.30	Solar Heat Gain Coefficient 0.22	
ADDITIONAL PERFORMANCE RATINGS		
Visible Transmittance 0.51	—	
Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information. www.nfrc.org		

NFRC LABELS

Buena Vista Sliding Doors
DS-DS, DS-3/16, 3/16-3/16
 LowE3 Glass with Argon Gas

DS = Double Strength (1/8, 3mm)
 3/16 = 4.7mm

 National Fenestration Rating Council® CERTIFIED	Crystal Pacific Window & Door System, Inc. Vista / Vista PLUS Sliding Door Vinyl Frame Double Glazing (DS-3/16)-Argon-LoE ³ -366™ CPW-M-2-00019-00001	
	ENERGY PERFORMANCE RATINGS	
U-Factor (U.S./I-P) 0.30	Solar Heat Gain Coefficient 0.22	
ADDITIONAL PERFORMANCE RATINGS		
Visible Transmittance 0.51	—	
Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information. www.nfrc.org		

 National Fenestration Rating Council® CERTIFIED	Crystal Pacific Window & Door System, Inc. Vista / Vista PLUS Sliding Door Vinyl Frame Double Glazing (3/16-3/16)-Argon-LoE ³ -366™ CPW-M-2-00018-00001	
	ENERGY PERFORMANCE RATINGS	
U-Factor (U.S./I-P) 0.29	Solar Heat Gain Coefficient 0.22	
ADDITIONAL PERFORMANCE RATINGS		
Visible Transmittance 0.50	—	
Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information. www.nfrc.org		

For informational purposes only. Subject to change without notice.