



Frame Depth: 5 1/4" | Overall Glass: 1"

Types & Styles
(Outside View)




2PD 2-Panel
XO, OX



3PD 3-Panel
XOO, OOX



3PD 3-Panel
OXOL, OXOR



4PD 4-Panel*
OXXOL, OXXOR

X = Vent Panel
O = Fixed Panel

*Special vent size available.

Min & Max Sizes

	MIN	MAX
2PD	60 x 70"	96 x 96" (120 x 82", PG20)
3PD	90 x 70"	144 x 92"
4PD Retro	120 x 70"	187.5 x 92"
4PD Nail	120 x 70"	189 x 92"
4PD Block	120 x 70"	192 x 92"

Performance Summary

STRUCTURAL	Up to PG 25 (DP 25)
ENERGY, LE3/Ar	(1/8-1/8) U-Factor 0.30, SHGC 0.22 (1/8-3/16) U-Factor 0.30, SHGC 0.22
ACOUSTIC	(1/8-3/16) STC 32, OITC 26 (3/16-1/4) STC 34, OITC 27

Features

QUALITY VINYL

15-point inspection program for quality assurance.

EFFICIENT DESIGN

Multichambered frame and interlocking sash with weather strips provide strength and efficiency.

ENERGY-EFFICIENT GLASS

Insulated glass (dual pane) unit with a high-performance stainless steel spacer system. 1/8 tempered glass is standard.

USER-FRIENDLY SASH

Includes durable dual-point locking, sturdy crescent handle, and easy sliding with end-adjustable dual steel rollers.

BETTER SCREENS

Quality aluminum screen door with a wide weather strip.

Options

ENHANCE ANY COLOR SCHEME

CrystalCoat™ exterior colors available with white interior.

INCREASE ENERGY EFFICIENCY

LowE3 performance glass with Argon gas (LE3/Ar) available.

IMPROVE ACOUSTICAL PROPERTIES

Dissimilar glass units with 1/8 and 3/16 glass available.

UPGRADE HARDWARE

Dual-point lock set and rollers available in stainless steel.

DIVIDE LITES WITH STYLE

Between-the-glass aluminum grids, 5/8" flat or 1" sculptured.

ADD PRIVACY & BEAUTY


Semi-opaque patterned and tinted specialty glass available.

Frame (Sill) Cross Sections

NAIL-ON.....1 1/4" nail fin and 1" setback, 3/16" stucco key.


RETROFIT.....2 1/16" dual-wall flush fin (z-bar), 3-sides is standard (4-sides available).

BLOCK.....No fin.



Nail-on


Monorail track with stainless steel cap shown.



Retrofit


4th z-bar shown (4-sides).

Dual Roller Profile




End-adjustable.

Handle Profiles



Keylock available.



Block

Threshold (sill) height, 1 11/16".

Screens are not fall prevention devices.

Subject to change without notice.
Check all applicable local codes.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.