


Viewed from exterior. Left or right hinged (active door).



37.25 x 81"

Single



63.5 x 81"

Sidelites



73.5 x 81"

Double*

Front Entry Doors

Prehung & Prefinished // Replacement Applications

FIBERGLASS SINGLE, WITH SIDELITES & DOUBLE

LOW-MAINTENANCE, NONDECAYING

High-quality fiberglass construction with no exposed wood to rot.

REINFORCED FIBERGLASS SKINS

Polyurethane foamcore and composite stiles and rails.

BEAUTIFUL & DURABLE FACTORY FINISHES

Authentic mahogany wood-grain look and embossed grain with edge banding.

JAMBS FINISHED TO MATCH

Composite jamb. Two depths available: 4.5625 or 5.25 in. (Door slab thickness: 1.75 in.)

MATCHING HINGES, CAMING, SHOE & SILL

Choose Dark Bronze or Zinc (Silver) heavy-duty ball bearing hinges, aluminum door shoe with drip cap, and adjustable aluminum sill.

ENERGY-EFFICIENT DECORATIVE GLASS

Triple-glazed LowE tempered glass with Argon gas. Factory glazed with no plugs.

20-YEAR LIMITED WARRANTY


5-year on glass, 2-year on finish. See front entry door warranty for details.

BRICK MOULD AVAILABLE

Finished-to-match composite exterior trim. Width: 2 in.

CASING AVAILABLE

Finished-to-match composite interior trim. Width: 2.875.

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



crystalpacificwindow.com/download

REF-FGD-051319 © CRYSTAL WINDOW & DOOR SYSTEMS

For informational purposes only. Subject to change without notice.

MODELS & OPTIONS

FM200I, FM200W, FM300A

- Dark Walnut or Medium Walnut
- Single, Sidelites or Double

FM200P

- Dark Walnut or Medium Walnut
- Single or Double

FM280D

- Dark Walnut, Mahogany or White*
- Single, Sidelites or Double***

FM285B

- Dark Walnut or Mahogany
- Single or Double***

FM800A

- Dark Walnut or Mahogany
- Single, Sidelites or Double***

*Sidelites not available in White.

***Special double door size available: 61.5 x 81 in. (models FM280D, FM800A, and FM285B only).

All prebored. Bore: 2.125 in. Backset: 2.375 in. Center/Center: 5.5 in.

Custom sizes and configurations and other options not available.

ENERGY PERFORMANCE

U-FACTOR: 1/4 Lite < 410 - LE/Ar DR 0.21, SL 0.26

SHGC: 1/4 Lite < 410 - LE/Ar DR 0.09, SL 0.14

U-FACTOR: 1/2 Lite < 900 - LE/Ar DR 0.25, SL 0.32

SHGC: 1/2 Lite < 900 - LE/Ar DR 0.15, SL 0.23

U-FACTOR: 3/4 Lite < 1100 - LE/Ar DR 0.28, SL 0.38

SHGC: 3/4 Lite < 1100 - LE/Ar DR 0.20, SL 0.32

U-FACTOR: Full Lite > 1100 - LE/Ar DR 0.32, SL 0.43

SHGC: Full Lite > 1100 - LE/Ar DR 0.26, SL 0.40

TRIM PROFILE

Brick Mould & Casing

