


Viewed from exterior. Left or right hinged (active door).




37.25 x 81"

Single



63.5 x 81"

Sidelites



73.5 x 81"

Double*

Front Entry Doors

Prehung & Prefinished // Replacement Applications

FIBERGLASS SINGLE, WITH SIDELITES & DOUBLE

LOW-MAINTENANCE, NONDECAYING

High-quality fiberglass construction with no exposed wood to rot.

REINFORCED FIBERGLASS SKINS

Polyurethane foamcore and composite stiles and rails.

BEAUTIFUL & DURABLE FACTORY FINISHES

Authentic mahogany wood-grain look and embossed grain with edge banding.

JAMBS FINISHED TO MATCH

Standard 4-9/16" or 5-1/4" composite jamb.
(Door slab 1-3/4".)

MATCHING HINGES, CAMING, SHOE & SILL

Dark Bronze or Zinc (Silver) heavy-duty ball bearing hinges, aluminum door shoe with drip cap, and adjustable aluminum sill.

ENERGY-EFFICIENT DECORATIVE GLASS

Triple-glazed LowE tempered glass with Argon gas.
Factory glazed with no plugs.

20-YEAR LIMITED WARRANTY

5-year on glass, 2-year on finish. See front entry door warranty for details.

BRICK MOULD AVAILABLE

2" finished-to-match composite exterior trim.

CASING AVAILABLE

2-7/8" finished-to-match composite interior trim.

MODELS & OPTIONS

FM200I, FM200W, FM300A

- Dark Walnut or Medium Walnut
- Single, Sidelites or Double

FM200P

- Dark Walnut or Medium Walnut
- Single or Double

FM280D

- Dark Walnut, Mahogany or White*
- Single, Sidelites or Double***

FM285B

- Dark Walnut or Mahogany
- Single or Double***

FM800A

- Dark Walnut or Mahogany
- Single, Sidelites or Double***

*Sidelites not available in White.

***Double door size 61.5 x 81" available with FM280D, FM800A, FM285B.

All prebored, 2-1/8" bore, 2-3/8" backset, 5-1/2" center/center.

Custom sizes and configurations and other options not available.

ENERGY PERFORMANCE

U-FACTOR: 1/4 Lite < 410 - LE/Ar DR 0.21, SL 0.26

SHGC: 1/4 Lite < 410 - LE/Ar DR 0.09, SL 0.14

U-FACTOR: 1/2 Lite < 900 - LE/Ar DR 0.25, SL 0.32

SHGC: 1/2 Lite < 900 - LE/Ar DR 0.15, SL 0.23

U-FACTOR: 3/4 Lite < 1100 - LE/Ar DR 0.28, SL 0.38


SHGC: 3/4 Lite < 1100 - LE/Ar DR 0.20, SL 0.32


U-FACTOR: Full Lite > 1100 - LE/Ar DR 0.32, SL 0.43

SHGC: Full Lite > 1100 - LE/Ar DR 0.26, SL 0.40

TRIM PROFILE

Brick Mould & Casing



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



crystalpacificwindow.com/download

REF-FGD-110518 © CRYSTAL WINDOW & DOOR SYSTEMS

For informational purposes only. Subject to change without notice.