


Viewed from the outside. Left or right hinged.




37 1/4 x 81"

Single



63 1/2 x 81"

Sidelites



73 1/2 x 81"

Double*



The Clear Choice Is Crystal

Fiberglass Front Entry Doors

Prehung & Prefinished | Replacement Applications

SINGLE, SINGLE WITH SIDELITES & DOUBLE

LOW-MAINTENANCE, NONDECAYING

High-quality fiberglass construction with no exposed wood to rot.

REINFORCED FIBERGLASS SKINS

Polyurethane foamcore and composite stiles and rails.

BEAUTIFUL & DURABLE FACTORY FINISHES

Authentic mahogany wood-grain look and embossed grain with edge banding.

JAMBS FINISHED TO MATCH

Standard 4 9/16" or 5 1/4" composite jamb.

MATCHING HINGES, CAMING, SHOE & SILL

Dark Bronze or Zinc (Silver) heavy-duty ball bearing hinges, aluminum door shoe with drip cap, and adjustable aluminum sill.

ENERGY-EFFICIENT DECORATIVE GLASS

Triple-glazed LowE tempered glass with Argon gas. Factory glazed with no plugs.

20-YEAR LIMITED WARRANTY

5-year on glass, 2-year on finish. See front entry door warranty for details.

BRICK MOULD AVAILABLE

2" finished-to-match composite exterior trim.

CASING AVAILABLE

2 7/8" finished-to-match composite interior trim.

AVAILABLE MODELS

FM200I, FM200W, FM300A

- Dark Walnut or Medium Walnut
- Single, Sidelites or Double

FM200P

- Dark Walnut or Medium Walnut
- Single or Sidelites

FM280D, FM800A

- Dark Walnut, Mahogany or White
- Single, Sidelites or Double*

FM285B

- Dark Walnut or Mahogany
- Single or Double*

*61 1/2 x 81" available with double FM280D, FM800A, FM285B.

All prebored and subject to availability at any given time.

Other models, sizes, and options not available.

ENERGY PERFORMANCE

U-FACTOR: 1/4 Lite < 410 - LE/Ar DR 0.21, SL 0.26
SHGC: 1/4 Lite < 410 - LE/Ar DR 0.09, SL 0.14

U-FACTOR: 1/2 Lite < 900 - LE/Ar DR 0.25, SL 0.32
SHGC: 1/2 Lite < 900 - LE/Ar DR 0.15, SL 0.23

U-FACTOR: 3/4 Lite < 1100 - LE/Ar DR 0.28, SL 0.38
SHGC: 3/4 Lite < 1100 - LE/Ar DR 0.20, SL 0.32

U-FACTOR: Full Lite > 1100 - LE/Ar DR 0.32, SL 0.43
SHGC: Full Lite > 1100 - LE/Ar DR 0.26, SL 0.40

TRIM PROFILE (Brick Mould & Casing)

