

The Clear Choice Is Crystal

Type & Style			Minimum				Maximum							
			WIDTH	HEIGHT			WIDTH	HEIGHT						
4000 VISTA	HS	XO, OX	24	x	12	-	-	72	x	72	-	-	-	-
		XOX (1/4-1/2-1/4)	65	x	12	-	-	120	x	60	-	-	-	-
		XOX3 (1/3-1/3-1/3)	48	x	12	-	-	120	x	60	-	-	-	-
	SH	SH	12	x	24	-	-	47	x	84	-	-	-	-
		SH3 (1/3 VENT)	12	x	36	-	-	47	x	126	-	-	-	-
	PW	O (FIXED)	12	x	12	-	-	72	x	71	-	-	-	-
5000 VISTA PLUS	HS	XO, OX	27	x	20	-	-	72	x	72	-	-	-	-
		XOX (1/4-1/2-1/4)	53	x	20	-	-	120	x	60	-	-	-	-
		XOX3 (1/3-1/3-1/3)	38	x	20	-	-	120	x	60	-	-	-	-
	SH	SH	20	x	27	-	-	47	x	84	-	-	-	-
		SH3 (1/3 VENT)	20	x	41	-	-	47	x	126	-	-	-	-
	PW	O (FIXED)	20	x	15	-	-	72	x	72	-	-	-	-
500	CA	CL, CR (CASEMENT)	16	x	18	-	-	36	x	72	-	-	-	-
		A (AWNING)	13	x	16	-	-	60	x	36	-	-	-	-
9000	SGD	2PD - XO, OX (LC 25)	60	x	70	-	-	96	x	96	-	-	-	-
		2PD - XO, OX (R 20)	60	x	70	-	-	120	x	82	-	-	-	-
		3PD - OXO, XOO, OOX	90	x	70	-	-	144	x	92	-	-	-	-
		4PD - OXXO, XOOX	120	x	70	-	-	192	x	92	-	-	-	-

Min-max under or over setup fee may apply.

Glass Thickness			Glass Limitations			
			SQ FT	SQ FT	MAX LENGTH (CANNOT BE EXCEEDED REGARDLESS OF THE SQUARE FOOTAGE)	
ANNEAL	SS	3/32 (2.2 mm)	<	12	72"	
	DS	1/8 (3.0 mm)	12	<	25	82"
	3/16	3/16 (4.7 mm)	25	<	40	96"
	1/4	1/4 (5.7 mm)		≥	40	120"
TEMP	DS	1/8 (3.0 mm)		<	25	84"
	3/16	3/16 (4.7 mm)	25	<	40	140"
	1/4	1/4 (5.7 mm)		≥	40	144"
SPL	5/32	Delta Frost, Flemish				83"
	3/16	Glue Chip, Rain				83"